

# Product Specifications For C0.7



## Power Rating

Maximum Power	13.3 kW
Maximum Torque	44 Nm @ 2400 rpm
Rated Speed	2200-3600 rpm
Minimum Power	8.8 kW

## Emission Standards

Emissions	U.S. EPA Tier 4 Final, EU Stage V
-----------	-----------------------------------

## General

Engine Configuration	In-Line 3
Bore	67 mm
Stroke	72 mm
Displacement	0.76 l
Compression Ratio	23.5:1
Aspiration	Naturally Aspirated (NA)
Combustion System	Indirect Injection
Rotation from Flywheel End	Counterclockwise

## Engine Dimensions - Approximate

Length	480 mm
Width	371 mm

**Height**

528 mm

**Weight - Net Dry - Basic Operating Engine Without Optional Attachments**

71 kg

## **C0.7 Standard Equipment**

### **Air Inlet**

Inlet manifold with choice of inlets.

### **Control System**

Alternator 12 volt 14 amp

Starter motor 12 volt

Glow plug starting aid

### **Cooling System**

Belt-driven coolant pump

Coolant temperature switch

Choice of cooling fans

### **Flywheel And Flywheel Housing**

SAE No. 6 1/2 flywheel

Choice of SAE No. 5 or standard backplate flywheel housing

### **Fuel System**

Fuel injection pump

Spin-on fuel filter

Electronic Shut-off Solenoid (ESOS)

### **Lube System**

Closed circuit breather

Spin-on lube oil filter

Lube oil pressure switch

Lube oil sump

### **General**

Cast iron, engine block

Cast iron exhaust manifold--side outlet

Cold start capability to -20° C (-4° F)

Gradeability 35° continuous

Paint: Caterpillar yellow, with optional colors available at request